



Detalles básicos de las válvulas a diafragma Saunders modelo vertedero tipo "A"

DIMENSIONES

Tamaño de la Válvula (DN)	Extremos Roscados Hembra			Extremos Bridados			Pesos (en Kg.)		
	A (mm)	B (máx)	B (máx)	A (mm)			B (máx)	ROSCA	BRIDA
				Metal	BS 5156 Cauchos	Rev. en Halar o vidrio			
Ho.Fo, Ho.N, Ho.M	Al. BC, ARB	Todos los Materiales							
8	48	48	59	-	-	-	-	0,150	-
10	48	48	68	-	-	-	-	0,260	-
15	64	64	91	108	-	110	100	0,525	1,550
20	83	83	94	117	123	119	100	0,850	2,250
25	108	95	111	127	133	129	110	1,400	2,950
32	121	114	152	146	152	148	150	2,200	3,800
40	140	133	164	159	165	161	160	2,700	4,750
50	165	152	187	190	196	192	180	4,150	7,750
65	203	191	224	216	222	218	214	10,300	13,200
80	254	241	233	254	260	256	220	15,650	19,060
100	-	-	-	305	311	307	300	-	32,030
125	-	-	-	356	361	358	375	-	45,000
150	-	-	-	406	412	408	430	-	67,000
200	-	-	-	521	527	523	507	-	141,000
250	-	-	-	635	641	637	588	-	240,000
300	-	-	-	749	755	751	683	-	329,000
350	-	-	-	749	755	751	893	-	429,100